

ALUMINUM ALLOY TECHNICAL SPECIFICATION SHEET

GENERAL: Standard packages are listed below by coil type and diameter. Many customers have applications and handling techniques that do not fit into the table below. We have many options that may fit your needs. Please discuss your unique situation with us and we will make every effort to meet your requirements.

AVAILABLE PACKAGE STANDARDS FOR INDIVIDUAL COILS

Package	Diameter (inches)	Dimensions (inches)			Individual Coils (lbs)
		Inside Dia.	Outside Dia.	Traverse	
22" Blockwound Coil	.051-.097	17	27	6	50-125
	.098-.187	17	28	10	75-125
30" Blockwound Coil	.188-.374	26	36	8	150-600
	.375-.530	26	36	12	150-600
36" Blockwound Coil	.500-.830	30	42	14	200-340
30" Orbital Coil	.063-.250	22	38	30-54 (ht)	600-1300
	.063-.250	22	38	18-30 (ht)	300-500
Straight Length Round	.080-.6875	6 inches to 12 foot in length			
Straight Length Hex	.125-.500	6 foot to 12 foot in length			

TYPICAL WEIGHTS ON STANDARD PACKAGES

Package	Diameter (inches)	Stretch Wrapped Coils		Unwrapped Coils in Boxes
		Steel Returnable Carrier	Corrugated Carrier	
22" Blockwound Coil	.051-.097	600	600	450
	.098-.187	600	600	450
30" Blockwound Coil	.188-.374	1000	-	450
	.375-.530	1000	-	450
36" Blockwound Coil	.500-.830	1200	-	-
30" Orbital Coil	.063-.250	600-1300	-	-
	.063-.250	300-500	300-500	-
Straight Length Round	.080-.6875	250# or 800# corrugated box, palletized		
Straight Length Hex	.125-.500	250# or 800# corrugated box, palletized		